

Loctite 409

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 12

SDS No.: 153513

V002.6 Revision: 29.05.2015

printing date: 29.11.2017

Replaces version from: 14.01.2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Loctite 409

#### **Contains:**

Ethyl 2-cyanoacrylate

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-products a fety.uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **Classification (CLP):**

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation. Target organ: respiratory tract irritation

#### 2.2. Label elements

### Label elements (CLP):

MSDS-No.: 153513 Loctite 409 Page 2 of 12

V002.6

Hazard pictogram:



Signal word: Warning

Hazard statement: H315 Causes skin irritation.

> H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Supplemental information** EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of

children.

**Precautionary statement:** P261 Avoid breathing vapours.

Prevention P280 Wear protective gloves/eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove **Precautionary statement:** 

Response contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in Disposal

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

#### 2.3. Other hazards

None if used properly.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### **General chemical description:**

Cyanoacrylate Adhesive

MSDS-No.: 153513 Loctite 409 Page 3 of 12

V002.6

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate	230-391-5	> 50-<100 %	Eye Irrit. 2
7085-85-0	01-2119527766-29		H319
			STOT SE 3
			H335
			Skin Irrit. 2
			H315
Bis(2-hydroxy-3-tert-butyl-5-	204-327-1	>= 0,1-< 0,9 %	Repr. 2
methylphenyl)methane	01-2119496065-33		H361
119-47-1			Aquatic Chronic 4
			H413
Hydroquinone	204-617-8	>= 0,01-< 0,1 %	Aquatic Acute 1
123-31-9	01-2119524016-51		H400
			Aquatic Chronic 1
			H410
			Carc. 2
			H351
			Muta. 2
			H341
			Acute Tox. 4; Oral
			H302
			Eye Dam. 1
			H318
			Skin Sens. 1
			H317
			M factor: 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Move to fresh air, consult doctor if complaint persists.

#### Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

#### Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

### Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

MSDS-No.: 153513 Loctite 409 Page 4 of 12

V002.6

### 4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

### 5.2. Special hazards arising from the substance or mixture

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### 5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not let product enter drains.

### 6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

## 7.2. Conditions for safe storage, including any incompatibilities

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

#### 7.3. Specific end use(s)

Adhesive

MSDS-No.: 153513 Loctite 409 Page 5 of 12

V002.6

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl 2-cyanoacrylate	0,3	1,5	Short Term Exposure		EH40 WEL
7085-85-0			Limit (STEL):		
[ETHYL CYANOACRYLATE]					

## **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment		Value	Value			Remarks
	Compartment	periou	mg/l	ppm	mg/kg	others	
Hydroquinone 123-31-9	aqua (freshwater)					0,114 μg/L	
Hydroquinone 123-31-9	aqua (marine water)					0,0114 μg/L	
Hydroquinone 123-31-9	sediment (freshwater)					0,98 μg/kg	
Hydroquinone 123-31-9	sediment (marine water)					0,097 μg/kg	
Hydroquinone 123-31-9	aqua (intermittent releases)					0,00134 mg/L	
Hydroquinone 123-31-9	soil					0,129 μg/kg	
Hydroquinone 123-31-9	STP					0,71 mg/L	

MSDS-No.: 153513 Loctite 409 Page 6 of 12

V002.6

### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl 2-cyanoacrylate 7085-85-0	Workers	Inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	Workers	Inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	Inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	Inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Hydroquinone 123-31-9	Workers	Dermal	Long term exposure - systemic effects		128 mg/kg bw/day	
Hydroquinone 123-31-9	Workers	Inhalation	Long term exposure - systemic effects		7 mg/m3	
Hydroquinone 123-31-9	Workers	Inhalation	Long term exposure - local effects		1 mg/m3	
Hydroquinone 123-31-9	general population	Dermal	Long term exposure - systemic effects		64 mg/kg bw/day	
Hydroquinone 123-31-9	general population	Inhalation	Long term exposure - systemic effects		1,74 mg/m3	
Hydroquinone 123-31-9	general population	Inhalation	Long term exposure - local effects		0,5 mg/m3	

#### **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Odor

Wear suitable protective clothing.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance liquid

Clear, colourless Sharp, irritating

Odour threshold No data available / Not applicable

MSDS-No.: 153513 Loctite 409 Page 7 of 12

V002.6

pH No data available / Not applicable

Initial boiling point > 150 °C (> 302 °F)

Flash point 80 - 93,3 °C (176 - 199.94 °F); Tagliabue closed cup

1,1 g/cm3

Decomposition temperature

No data available / Not applicable

Vapour pressure 0,6 mbar

(25 °C (77 °F))

Density (20 °C (68 °F))

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

Explosive properties

No data available / Not applicable
No data available / Not applicable
Polymerises in presence of water.

(Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable **Explosive limits** No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

#### 9.2. Other information

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

#### 10.5. Incompatible materials

None if used properly.

#### 10.6. Hazardous decomposition products

None if used for intended purpose.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

MSDS-No.: 153513 Loctite 409 Page 8 of 12

V002.6

### Inhalative toxicity:

May cause respiratory irritation.

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

#### Skin irritation:

Causes skin irritation.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

### Eye irritation:

Causes serious eye irritation.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Ethyl 2-cyanoacrylate	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7085-85-0						Oral Toxicity)
Bis(2-hydroxy-3-tert-	LD50	> 10.000 mg/kg	oral		rat	
butyl-5-						
methylphenyl)methane						
119-47-1						
Hydroquinone	LD50	367 mg/kg	oral		rat	OECD Guideline 401 (Acute
123-31-9						Oral Toxicity)

## Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute
7085-85-0						Dermal Toxicity)

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute
7085-85-0				Dermal Irritation / Corrosion)

### Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate	irritating	72 h	rabbit	OECD Guideline 405 (Acute
7085-85-0				Eye Irritation / Corrosion)

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	
Hydroquinone 123-31-9	sensitising	Guinea pig maximisat ion test	guinea pig	

MSDS-No.: 153513 Loctite 409 Page 9 of 12

V002.6

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Bis(2-hydroxy-3-tert- butyl-5- methylphenyl)methane 119-47-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroquinone 123-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)

## Reproductive toxicity:

Hazardous substances	Result / Classification	Species	Exposure	Species	Method
CAS-No.			time		
Bis(2-hydroxy-3-tert-	NOAEL $P = 12.5 \text{ mg/kg}$	screening		rat	OECD Guideline 421
butyl-5-		oral: gavage			(Reproduction /
methylphenyl)methane					Developmental Toxicity
119-47-1					Screening Test)

## Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroquinone 123-31-9	NOAEL=>= 250 mg/kg	oral: gavage	14 days5 days/week. 12 doses	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Hydroquinone 123-31-9	LOAEL=<= 500 mg/kg	oral: gavage	14 days5 days/week. 12 doses	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

# **SECTION 12: Ecological information**

## General ecological information:

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## 12.1. Toxicity

#### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

MSDS-No.: 153513 Loctite 409 Page 10 of 12

V002.6

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Hydroquinone 123-31-9	LC50	0,638 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydroquinone 123-31-9	EC50	0,134 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydroquinone 123-31-9	EC50	0,335 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline
Hydroquinone 123-31-9	NOEC	0,0057 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

## 12.2. Persistence and degradability

## Persistence and Biodegradability:

No data available for the product.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0		aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Bis(2-hydroxy-3-tert-butyl-5- methylphenyl)methane 119-47-1	under test conditions no biodegradation observ		0 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydroquinone 123-31-9	readily biodegradable	aerobic	75 - 81 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

## Mobility:

Cured adhesives are immobile.

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Ethyl 2-cyanoacrylate 7085-85-0	0,776				22 °C	EU Method A.8 (Partition Coefficient)
Bis(2-hydroxy-3-tert-butyl-5- methylphenyl)methane 119-47-1	6,24					Commonly
Hydroquinone 123-31-9	0,59					EU Method A.8 (Partition Coefficient)

#### 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Bis(2-hydroxy-3-tert-butyl-5-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
methylphenyl)methane	Bioaccumulative (vPvB) criteria.
119-47-1	
Hydroquinone	Not fulfilling PBT (persistent/bioaccummulative/toxic) criteria
123-31-9	

## 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

MSDS-No.: 153513 Loctite 409 Page 11 of 12

V002.6

Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

14.2.

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

## **SECTION 14: Transport information**

### 14.1. UN number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	3334

# UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods

IATA Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

## 14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
T 4 753 4	

IATA 9

### 14.4. Packaging group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods

IATA III

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

#### 14.6. Special precautions for user

ADR not applicable

MSDS-No.: 153513 Loctite 409 Page 12 of 12

V002.6

RID not applicable ADN not applicable IMDG not applicable

IATA Primary packs containing less than 500ml are unregulated by this mode of transport

and may be shipped unrestricted.

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 % (1999/13/EC)

#### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

### **Annex - Exposure Scenarios:**

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link:

 $http://mymsds.henkel.com/mymsds/.470833..en. ANNEX\_DE.15743123.0. DE.pdf$ 

Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.