

Loctite Corporation

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

7455 (Aerosol) 0178047A 5.00 IE EA 25.03.2003 MSDS_IE

This safety data sheet has been prepared in accordance with the requirements of EC Directives 1999/45/EC and 2001/58/EC and provides information relating to the safe handling and use of the product.

1. PRODUCT AND COMPANY INFORMATION

Product Code 0178047A

Trade Name 7455 (Aerosol)

Manufacturer/Supplier Henkel Loctite Adhesives Ltd.

Address Watchmead,

Welwyn Garden City,

Herts., AL7IJB.

UK

Phone Number 01 707 358800 Fax Number 01 707 358900

Emergency Phone Number +353-1-4599301/+353-87-2629625/+353-1-4046444

2. COMPOSITION / INFORMATION ON INGREDIENTS

Nature Solvent based activator.

Hazardous Components in Product for EC

Component Name CAS / EINEC Concentration R Phrases Classification

Heptane 142-82-5 205- 60.00 - 90.00 R11, R38, R65, F, Xn, N 563-8 R67, R50/53

Propane 74-98-6 200- 10.00 - 15.00 R12 F+

827-9

3. HAZARD IDENTIFICATION

Extremely flammable.

Irritating to skin. Solvent will have a defatting action on the skin making it more susceptible to dermatitis and sensitisation. Inhalation of vapours may cause headaches or dizziness.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The aerosol container is under pressure. Do not expose to high temperatures.

4. FIRST AID MEASURES

First Aid - Inhalation

Remove affected person to fresh air, and if still feeling unwell seek medical attention.

First Aid - Skin

Wash skin with plenty of soap and water and apply replenishing cream if necessary. Seek medical advice if irritation develops.

First Aid - Eyes

Flush eyes with plenty of water for at least 15 minutes. If irritation persists seek medical attention.

First Aid - Ingestion

Rinse mouth with water then give plenty of water to drink. Do not induce vomiting. Seek medical advice.

5. FIRE FIGHTING MEASURES

This product is extremely flammable. Keep unaffected containers cool with water spray. If product is involved in fire extinguish with dry powder, foam or carbon dioxide. Self contained breathing apparatus should be worn when dealing with fire. Aerosol containers may explode when exposed to high temperatures.



7455 (Aerosol)

0178047A 5.00 IE EA 25.03.2003 MSDS_IE

Loctite Corporation

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

6. ACCIDENTAL RELEASE MEASURES

Ventilate area. Eliminate sources of ignition.

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. HANDLING AND STORAGE

Handling

Avoid sources of ignition - no smoking. Vapours should be extracted to avoid inhalation. Avoid contact with skin and eyes.

Storage

Keep away from sources of ignition. Store away from heat in a cool, well-ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

HSA (2002).C.O.P.: OEL 400 ppm,(1600 mg/m3) 8h TWA

HSA (2002).C.O.P.: OEL 500 ppm,(2000 mg/m3) 15 min

exposure limit.

ACGIH: TLV 400ppm 8h TWA. ACGIH: STEL 500ppm 15min TWA.

Use in well ventilated area. Good industrial hygiene practices should be observed. In circumstances where there is a potential for prolonged or repeated skin contact, the use of polyvinyl chloride or nitrile rubber gauntlets or equivalent solvent resistant gloves is recommended. Safety glasses should be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Colour
Colour
Colourless.
Pungent.

pH Not applicable.

Boiling Range/Point (°C) 97 to 99.

Flash Point (CC) (°C) Not applicable for an aerosol

Specific Gravity 0.68 g/cm3 at 20 °C.

Solubility in Water (kg/m³) Immiscible.

Solubility in Acetone Miscible

Vapour Pressure (mmHg 35 at 20 °C.

@25°C)

Explosion Limits (%) 1 to 7.

10. STABILITY AND REACTIVITY

The product is relatively stable under normal conditions of use. Non reactive to oxidising agents except for peroxides.

11. TOXICOLOGICAL INFORMATION

Inhalation

Inhalation of vapours may cause headaches or dizziness.



Loctite Corporation

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

7455 (Aerosol)

0178047A 5.00 IE EA 25.03.2003 MSDS_IE

11. TOXICOLOGICAL INFORMATION

Skin

May cause irritation to skin. Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eves

May cause mild irritation to the eyes.

Ingestion

Ingestion of large quantities may cause liver or kidney damage.

12. ECOLOGICAL INFORMATION

The product should not go into drains or surface water.

Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Avoid disposing of the container, even when empty, into the environment. Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

UN Number 1950

Air (IATA) Aerosols, flammable, n.o.s., Class 2.1, flammable gas.

Sea (IMO) Aerosol, Class 2, EmS F-E, S-U.

Road (ADR)/Rail (RID) Aerosol, Flammable liquid, Class 2 Classification code:

5F

15. REGULATORY INFORMATION

Contains

Labelling Information



Extremely flammable



Irritant



Dangerous for the Environment

R phrases R12 Extremely flammable.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-

term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

S phrases S16 Keep away from sources of ignition - No Smoking.

S23 Do not breathe spray.

S28 After contact with skin, wash immediately with plenty

of soap and water.

S61 Avoid release to the environment. Refer to special

instructions/Safety data sheets.

Voluntary Labelling Pressurised container: protect from sunlight and do not

expose to temperatures exceeding

+50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent

material.

16. OTHER INFORMATION

MSDS data revised 25 March 2003



7455 (Aerosol)

0178047A 5.00 IE EA 25.03.2003 MSDS_IE

Loctite Corporation

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

Hazardous Components in Product for EC

 Component Name
 R Phrases

 Heptane
 R11, R38, R65, R67, R50/53

 Propane
 R12

R11 R11 Highly flammable.
R12 R12 Extremely flammable.
R38 R38 Irritating to skin.

R50/53 R50/53 Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

R65 R65 Harmful: may cause lung damage if swallowed.
R67 R67 Vapours may cause drowsiness and dizziness.

Prepared by:

Vanessa Doherty HRA Specialist Health & Regulatory Affairs - Europe Further Information may be obtained from:-

Loctite Corporation, Health and Regulatory Affairs - Europe, Tallaght Business Park, Whitestown, Dublin 24, Ireland.

Tel: +353-1-4046444. Fax: +353-1-4510806.

The information in this safety data sheet was obtained from reputable sources and to the best of our knowledge is accurate and current at the mentioned date. Neither Loctite nor its subsidiary companies accept any liability arising out of the use of the information provided here or the use, application or processing of the product(s) described herein. Attention of users is drawn to the possible hazards from improper use of the product(s). This safety data sheet was prepared in accordance with Commission Directive 2001/59/EC adapting to technical progress for the 28th time Council Directive 67/548/EEC and Commission Directive 1999/45/EC.