



SC01

February 2012

PRODUCT DESCRIPTION

SC01 provides the following product characteristics:

Technology	Cleaner
Application	Pb-free soldering

SC01 high performance cleaning solution is developed for solder paste cleaning processes. This material can be used manually or with an automatic stencil underside wiper.

FEATURES AND BENEFITS

- Reduced VOC
- Fast evaporating
- High solvency
- No oily residues
- Low environmental impact

SC01 can be used for manual cleaning of reworked circuit assemblies.

Screen/stencil cleaning equipment	Recommended
Printer automatic wipe system	Suitable
Manual cleaning operation	Suitable
Rework	Suitable

TYPICAL PROPERTIES

SC01 are based on user-friendly oxygenated organic chemistries. Each product is designed with slightly different properties to suit a particular application.

Cleaner Typical Properties

Relative Density	0.896
Flashpoint, °C	40
Evaporation (Butyl Acetate=100)	46
Appearance	Clear and colorless
Odor	Characteristic
Water solubility	Miscible

DIRECTIONS FOR USE

These materials clean by dissolution of the organic media present in the paste and, as such, will dissolve a wide variety of organic materials. Check compatibility of the cleaner with all encountered materials before use. The following table provides compatibility guidelines.

SC01 will remove paint from the following surfaces.

Acrylonitrile butadiene styrene	Good compatibility
Butyl rubber	Good compatibility
Epoxy adhesives	Good compatibility
Fiducial epoxies	Good compatibility
Natural rubber	Good compatibility
Nitrile rubber	Good compatibility
Nylon	Good compatibility
P.U. squeegee	Good compatibility
Polycarbonate	Good compatibility
Polyethylene	Good compatibility
Polypropylene	Good compatibility
Polytetrafluoroethylene	Good compatibility
PTFE squeegee	Good compatibility
SBR rubber	Good compatibility
EPDM rubber	Do not use
Polymethylmeth acrylate	Do not use
Polystyrene	Do not use
PVC	Do not use
Silicone rubber	Do not use

ENVIRONMENTAL

All materials used in this product has low environmental impact. They are biodegradable and unlikely to bioaccumulate. The water hazard classification under the German WGK is class 1 for all components, while the TA luft air class is III, the lowest category. Biodegradability as % of THOD is 84% in 28 days.

PACKAGING

Containers: SC01 is supplied in:

- 500 ml trigger spray packs
- 11, 51 and 251 polythene containers

Other packaging types may be available on request; please contact your local technical service helpdesk for assistance.

Shelf Life:

The stable formulation and components of SC01 ensure a minimum shelf life of one year in an unopened container.

DATA RANGES

The data contained herein may be reported as a typical value and/or a range. Values are based on actual test data and are verified on a periodic basis.

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).



Not for Product Specifications

The technical information contained herein is intended for reference only. Please contact Henkel Technologies Technical Service for assistance and recommendations on specifications for this product.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation and its affiliates ("Henkel") specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel products. Henkel specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

All trademarks in this document are trademarks and/or registered trademarks of Henkel in the US and elsewhere.

Reference 0.0